

Two machines.
One thousand ways
to get it done.

MEIKO's Variotronic™
DV 120.2 & DV 120.2T
are, simply put, the
industry's most
versatile door type
machines, ever.



LOW - FINE GLASSWARE

At only 7 PSI, and using MEIKO's Soft Start feature that gradually builds wash pressure, fine glassware and china is protected from sudden shifts that can cause breakage.

NORMAL - DISHES & GLASSWARE

The wash pressure is increased to 10 PSI to provide faster cleaning for normal dishes and glassware.

HIGH - UTENSILS & HEAVY SOIL

At 15 PSI and with an extended cycle, the DV 120.2 and DV 120.2 T can power through the toughest soil on pots, pans, and utensils.



DV 120.2 | Variotronic™ Door Type

The DV 120.2 Variotronic™ door type machine transforms from a glasswasher, to a dishwasher, to a pot and pan washer — with the quick touch of a single button. User-selected wash pressures can easily accommodate a wide variety of ware.

CAPACITY:
Glassware: 34 racks/hr.,
1,224 glasses/hr.
Dishes: 54 racks/hr.,
1,350 dishes/hr.
Utensils: 20 racks/hr.


WATER CONSUMPTION:
61.0 gals./hr., 1.13 gals./rack

WATER SUPPLY TEMPERATURE:
Any; 140°F recommended

WASH PUMP:
2 hp.

OPTIONS:
Internal detergent/rinse aid
pumps, drain tempering, flanged
feet, external vent fan control

VOLTAGES:
208-230V / 60Hz / 1Ph
208-230V / 60Hz / 3Ph
460V / 60Hz / 3Ph



DV 120.2 T | Tall Hood Variotronic™ Door Type

Featuring a vertical clearance of 27", the DV 120.2 T combines Variotronic™ flexibility with the ability to accept taller ware, such as 18 x 26" sheet pans.

CAPACITY:
Glassware: 34 racks/hr.,
1,224 glasses/hr.
Dishes: 52 racks/hr.,
1,300 dishes/hr.
Utensils: 20 racks/hr.

WATER CONSUMPTION:
58.8 gals./hr., 1.13 gals./rack

WATER SUPPLY TEMPERATURE:
Any; 140°F recommended

WASH PUMP:
2 hp.

OPTIONS:
Internal detergent/rinse aid
pumps, drain tempering, flanged
feet, external vent fan control

VOLTAGES:
208-230V / 60hz / 3ph
460V / 60hz / 3ph

