



**DV 80.2 | Door Type**



**DV 80.2 WAHR | Ventless Door Type**

**DV 200.2 | Dual Rack Door Type**

Our DV 80.2 combines fast loading and improved ventilation with the advanced features that come standard on our door type machines.

**CAPACITY:**  
61 racks/hr., 1,525 dishes/hr.

**WATER CONSUMPTION:**  
45.1 gals./hr., 0.74 gals./rack

**WATER SUPPLY TEMPERATURE:**  
Any; 140°F recommended

**WASH PUMP:**  
1 hp., Tank heat 6 kW,  
Booster heat 9 kW

**OPTIONS:**  
Internal detergent/rinse aid pumps,  
drain tempering, flanged feet, external  
vent fan control

**VOLTAGES:**  
208-230V / 60Hz / 1Ph  
208-230V / 60Hz / 3Ph  
460V / 60Hz / 3Ph

Our DV 80.2 with Waste Air Heat Recovery reclaims energy from the machine to heat incoming water. This efficient design can run on a **cold water supply** & requires no special ventilation.\*

**CAPACITY:**  
40 racks/hr., 1,000 dishes/hr.

**WATER CONSUMPTION:**  
29.6 gals./hr., 0.74 gals./rack

**WATER SUPPLY TEMPERATURE:**  
Cold water; 70°F recommended

**WASH PUMP:**  
1 hp., Tank heat 6 kW,  
Booster heat 9 kW

**OPTIONS:**  
Internal detergent/rinse aid pumps,  
drain tempering, flanged feet, external  
vent fan control

**VOLTAGES:**  
208-230V / 60Hz / 1Ph  
208-230V / 60Hz / 3Ph  
460V / 60Hz / 3Ph

\*Subject to local building codes.

The DV 200.2 holds two 20 x 20" racks per cycle, and also accommodates 18 x 26" sheet pans. This machine is the perfect solution to fill the gap between a traditional door type unit and a small rack conveyor machine.

**CAPACITY:**  
108 racks/hr., 2,700 dishes/hr.

**WATER CONSUMPTION:**  
115.6 gals./hr., 1.07 gals./rack

**WATER SUPPLY TEMPERATURE:**  
Any; 140°F recommended

**WASH PUMP:**  
2 x 1 hp.

**OPTIONS:**  
Internal detergent/rinse aid pumps,  
drain tempering, flanged feet, external  
vent fan control

**VOLTAGES:**  
208-230V / 60Hz / 3Ph  
460V / 60Hz / 3Ph

